

tesa® Powerstrips Self-Adhesive Hooks L Classic

Product Information

BNR 58051, 58010

Product Description

tesa Powerstrips Hooks Classic are removable towel hooks. Use these self-adhesive towel hooks as versatile solution for bathroom and kitchen.

Product Features

- · Easy to mount without drilling, screws or nails
- · Strong hold up to 2 kg
- Removable without trace thanks to the Powerstrips® technology
- Made from high quality plastic
- Usable on tiles, glass, wood, plastic and a variety of other surfaces*
- Hooks reusable with tesa Powerstrips® LARGE
- Completely covered tesa Powerstrip®

Application Fields

How to apply - Step by step: 1. Clean the surface with alcohol or silicone-free glass cleaner

- 2. Apply the Powerstrip Large strip on the surface press for 5 seconds minimum
- 3. Disengage the base plate of the hook and stick it onto the strip press for 5 seconds minimum
- 4. Let the hook slide down on the base plate until it is locked

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	•	Hook shape	Rectangular
•	Holding power up to	2 Kg	•	Silicone free	yes

^{*}Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material



tesa® Powerstrips Self-Adhesive Hooks L Classic

Product Information

Properties/Performance Values

Application temperature from	+15 °C	 Residue-free removability 	yes
 Application temperature to 	+35 °C	 Reusable 	yes
 Applicationfield 	Bathroom, Kitchen	 Reusable with 	Powerstrips Large
 Area of use 	Indoor	 Solvent free 	yes
 Batteries included 	no	 Suitable surfaces 	Glazed Tiles, Glass,
 Batteries required 	no		Even wood, Steel,
 Chemical Resistance 	no		Acrylic glass, Most
 Hazard material 	no		plastics, Metal
 Humidity sealing 	no	 Temperature resistance 	yes
 Material 	PS (polystyrene)	 Temperature resistance max. 	35 °C
 Oil and grease resistance 	no	 Temperature resistance min. 	15 °C
 Ozone resistance 	no	 UV resistant 	no
		 Water resistance 	no
		 Waterproof 	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

