

tesa® Adhesive Strips for Wallpaper & Plaster 1kg



Product Information

BNR 77771

Product Description

Refill pack for the Adhesive Nail for Wallpaper & Plaster 1kg. For convenient reuse of the Adhesive Nail. The clever way to hang pictures.

Product Features

- Strip for reuse* of the Adhesive Nail for Wallpaper & Plaster 1kg
- · For textured and sensitive surfaces like wallpaper or plaster
- For objects up to 1 kg** per strip
- · Removable without a trace

Application Fields

How to apply – Step by step1. Get the most out of an Adhesive Strip by cleaning the surface of dirt and dust with a dust-free cloth.

- 2. The Adhesive Strip for Wallpaper & Plaster should be applied to the rougher surface first. So when it comes to wallpaper or plaster, always apply it to the wall, with the blue tab facing the wall. Before using a strip, make sure that your surface is strong enough to take the weight of the object you want to attach.
- 3. Press down evenly over the entire strip for at least 5 seconds, and only then remove the protective foil. Pressing down like this activates the flexible polymer chains that form U-shaped links with the surface. It's these links that give such a secure and reliable bond, so the harder and more evenly you press, the better the bond.
- 4. Now apply the tesa® Adhesive Nail by aligning it on the top edge of the strip, then folding it down. Press down evenly all over the entire nail for at least 5 seconds.
- 5. The tab should be left accessible below the nail for easy removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Type of adhesive synthetic rubber
Total thickness 1350 μm
Holding power up to 1 Kg
Silicone free yes

Holding power of strip up to
1 Kg

^{*}Only for use with an Adhesive Nail

^{**}For optimal results please read instruction leaflet



tesa® Adhesive Strips for Wallpaper & Plaster 1kg

Product Information

Properties/Performance Values

•	Application temperature from	-15 °C	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	no
•	Batteries included	no	•	Reusable with	_NULL
•	Batteries required	no	•	Solvent free	yes
•	Chemical Resistance	no	•	Suitable surfaces	Wallpaper, Plaster
•	Hazard material	no	•	Temperature resistance max.	35 °C
•	Humidity resistance	no	•	Temperature resistance min.	5°C
•	Oil and grease resistance	no	•	UV resistant	no
•	Ozone resistance	no	•	Waterproof	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

