



tesa[®] 64439

Product Information

Repulpable double-sided tape

Product Description

tesa[®] 64439

Product Features

- Very good adhesion values on coated and uncoated papers
- Good tack properties
- Good repulpability of the tape over full pH-range (pH3 –pH9), the liner is non-repulpable

Application Fields

tesa[®] 64439 is particularly suitable for

- # Static splices
- # Permanent splices
- # Core starting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-------|
| • Backing | non-woven | • Total thickness | 56 µm |
| • Type of adhesive | modified acrylic | • Color | blue |
| • Type of liner | glassine | | |

Properties/Performance Values

- | | | | |
|-----------------------------------|-----------|--------|-----|
| • Shelf life time (packed) < 25°C | 12 months | • Tack | low |
| • Static shear resistance | low | | |



tesa[®] 64439

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64439>