



tesa[®] 58377

Product Information

50µm Single-Sided Black Flame-Retardant PET Tape

Product Description

tesa[®] 58377BK is a 50µm Single-Sided Black Flame-Retardant PET Tape. It is equipped with flame retardant acrylic and a black PET backing. Its PE coated liner also ensures good convertability.

Product Features

- Outstanding flame retardancy performance (VTM 0) according to UL94
- Very good electrical insulation property
- Reliable adhesion strength on polar substrate
- Friendly to converting process

Application Fields

- Electrical insulation in Battery system with additional flame retardant property (VTM 0)
- Wrapping or encapsulation

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------|----------------------|--------|
| • Backing | PET | • Total thickness | 50 µm |
| • Type of adhesive | FR acrylic | • Thickness of liner | 140 µm |
| • Type of liner | PE-coated paper | | |

Properties/Performance Values

- | | | | |
|-----------------------------------|--------|-------------------------------------|--------|
| • Elongation at break | 88 % | • Temperature resistance long term | 70 °C |
| • Dielectric breakdown voltage | 4500 V | • Temperature resistance short term | 125 °C |
| • Static shear resistance at 23°C | good | | |

Adhesion to Values

- | | | | |
|-----------------------------|----------|------------------------|----------|
| • Aluminium (initial) | 5 N/cm | • ASTM (initial) | 6 N/cm |
| • Aluminium (after 14 days) | 6.2 N/cm | • ASTM (after 14 days) | 6.8 N/cm |



tesa[®] 58377

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58377>