



tesa[®] 4448

Product Information



Repulpable single-sided tape

Product Description

tesa[®] 4448 is a single-sided repulpable tape without a liner consisting of a flat-back paper and a modified water soluble acrylic adhesive.

Color: White

Product Features

- Very high tack properties
- High shear strength
- Strong flat paper backing for reliable performance on even higher paper grammages
- Full repulpability over full pH-range (pH3 – pH9) for unrestricted use in paper-, board- and fluff-pulp production
- Paper from well-managed certified forests and other controlled sources

Application Fields

tesa[®] 4448 is particularly suitable for:

- End tabbing of fluff-pulp
- End tabbing, splicing and web feeding of paper-based substrates

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|-------------------|--------|
| • Backing | flat paper | • Type of liner | none |
| • Type of adhesive | repulpable tackified acrylic | • Total thickness | 165 µm |

Properties/Performance Values

- | | | | |
|-----------------------------------|-----------|--------------------------------|-----------|
| • Elongation at break | 3 % | • Static shear resistance | good |
| • Tensile strength | 110 N/cm | • Tack | very good |
| • Shelf life time (packed) < 25°C | 12 months | • Tensile strength (crosswise) | 70 N/cm |

For latest information on this product please visit <http://l.tesa.com/?ip=04448>



tesa[®] 4448

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04448>