tesa® ALUXX shower rack, self-adhesive, chromed aluminium

Product Information

BNR 40211

Product Description

The self-adhesive tesa® Aluxx shower rack is reliably wall-mounted with little effort. Drilling is not required, leaving walls and tiles undamaged. The rack can be taken down at any time, with no trace remaining, and remounted elsewhere with a new adapter BK43-2. It's a beautiful, glossy bath accessory.

Product Features

- Shower rack, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated aluminum, round style, circular wall plates
- Reliable hold, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Quick removal, without a trace, conveniently reusable with new adapter BK43-2
- Simple application, no drilling needed
- Product dimensions: 260mm x 180mm x 107mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of adhesive	Silane modified polymer	• Hook shape	Round
• Holding power up to	5 Kg		

Properties/Performance Values

• Applicationfield	Bathroom	• Residue-free removability	yes
• Area of use	Indoor	• Reusable	yes
• Batteries included	no	• Reusable with	Adapter BK43-2
• Batteries required	no	• Shape of wall piece	Round
• Chemical Resistance	no	• Solvent free	yes
• Curing time	12 hour(s)	• Suitable surfaces	Glazed Tiles, Marble, Glass, Metal, Stone, Concrete, Even wood, Most plastics
• Design series	tesa® ALUXX		
• Hazard material	yes		
• Material	Chromed Aluminium		
		• UV resistant	yes
		• Waterproof	yes

For latest information on this product please visit http://l.tesa.com/?cp=NaN

tesa® ALUXX shower rack, self-adhesive, chromed aluminium

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?cp=NaN