



tesapack[®] Transparent Promopack

Product Information

BNR 57529, 57229, 57456, 57008, 57455

Product Description

tesapack[®] standard is cost-effective carton sealing tape for typical household applications. It is ideal to seal lightweight packages and parcels.

Product Features

- PP backing
- Solvent-free adhesive
- Adequate sealing security
- Easy unwinding (noisy)
- Suitable for use in all tesa[®] hand dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 43 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------------------|-----------------------------|-----------|
| • Tensile strength | 35 N/cm | • Residue-free removability | no |
| • Adhesive strength | High adhesion | • Reusable | no |
| • Ageing resistance (UV) | yes | • Roll width max | 50 mm |
| • Applicationfield | Office, Home | • Serrated blade | _NULL |
| • Batteries included | no | • Solvent free | no |
| • Batteries required | no | • Spare part service | no |
| • Hand tearability | no | • Suitable surfaces | Cardboard |
| • Humidity resistance | no | • Tear resistance | yes |
| • Low noise unwinding | no | • Tensibility | 169 % |
| • Material | PP (polypropylene) | • Tension control | _NULL |
| • Max roll length | 66 m | • Writable | no |



tesapack[®] Transparent Promopack

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>