



tesafilm® Ultra strong

Product Information

BNR 57377, 57376

Product Description

tesafilm® ULTRA STRONG is a transparent and very powerful premium adhesive tape. That's why it's well suited for safely sealing larger letter envelopes, jiffy bags or packages. Moreover, bundling materials or minor repairs can be done without a problem.

Product Features

- Transparent adhesive tape in premium PVC quality
- Very powerful adhesive and tear-proof
- Can be rolled off smoothly and quietly
- High moisture resistance
- Suitable for all tesa Easy Cut® desk dispensers (33m or 66m, depending on size of the roll)
- Ideal for the secure sealing of letters, jiffy bags, packages etc. Also perfectly suited for repairing minor damages or bundling materials

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-------|
| • Backing | PVC film | • Total thickness | 65 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------------------|--|------------------|
| • Tensile strength | 60 N/cm | • Photocopy neutral | no |
| • Adhesive strength | Very high adhesion | • Residue-free removability | no |
| • Ageing resistance (UV) | no | • Reusable | no |
| • Applicationfield | Office, Home | • Roll width max | 15 mm |
| • Batteries included | no | • Serrated blade | _NULL |
| • Batteries required | no | • Solvent free | no |
| • Ecofriendly packaging | _NULL | • Suitable for right and/or left handers | _NULL |
| • Hand tearability | no | • Suitable surfaces | Paper, Cardboard |
| • Hazard material | no | • Tear resistance | yes |
| • Low noise unwinding | no | • Transparency | medium |
| • Material | PP (polypropylene) | • Unwind force | 2.8 N/cm |
| • Max roll length | 60 m | • Writable | no |

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>



tesafilm[®] Ultra strong

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>